



**Brightwater**  
FLY ANGLER

## **Brightwater Logotype Decal Instructions**

Congratulations on your new Brightwater Fly Angler Logotype Decal!

Your new decal can be applied to almost any glass or smooth surface.

Application instructions:

1. Be sure the surface temperature is between 50 and 90 degrees Fahrenheit before attempting the installation.
2. Clean the surface thoroughly with glass cleaner or mild dish detergent and warm water then dry thoroughly.
3. Peel the decal from backing (the side with the printed grid), this will expose the adhesive. Carefully position the decal and apply the sticky side to the glass or other surface.
4. Starting from the center, use a smooth edge (such as a credit card) to remove any excess air from between the decal and the surface.
5. Allow the decal adhesive to set for a 3 to 5 minutes.
6. Remove the backing application tape; always pull it slowly, back onto itself, at a 180-degree angle. Be careful that any small edges do not pull off with the backing.

Brightwater Fly Angler  
[www.brightwaterflyangler.com](http://www.brightwaterflyangler.com)  
[mark@brightwaterflyangler.com](mailto:mark@brightwaterflyangler.com)

Brightwater Fly Angler – P.O. Box 202 - Wasco, Illinois 60183  
630-532-0367 630-587-9837 fax  
[www.brightwaterflyangler.com](http://www.brightwaterflyangler.com)  
[mark@brightwaterflyangler.com](mailto:mark@brightwaterflyangler.com)